Manak Bhawan,9 Bahadur Shah Zafar

Marg,

Address

New Delhi, 110002

Phones

91-11-23239382

Fax:

91-11-23239382

E-mail:

fmcs@bis.org.in

Web:

http://www.bis.org.in

ATTACHMENT TO LICENCE NO. CM/L- 4051946

CML/NO	NAME OF THE LICENSEE WITH THE ADDRESS	NAME OF THE PRODUCT	IS NO.
	Wu Gong Bridge Vunlou Marchy Town	Plugs and socket outlets of rated voltage upto and including 250 velts and rated current upto and including 16 amperes, Specification	IS 1293:2005

ENDORSEMENT NO. 09 DATED 16-05-9020

Consequent upon the revision of IS 1293:2005 as IS 1293:2019, the Indian Standard number specified in the schedule of the licence stands revised as under with effect from Sixth May Two Thousand Twenty.

IS 1293:2019 Plugs and socket - petiets for household and similar purposes of rated voltage upto and including 250 volts and rated current upto and including 16 amperes. Specification

Consequent upon the above revision, the scope of the licence had been revised as under w.e.f. Sixth May Two Thousand Twenty

Moulded Plugs of fellowing varieties as per IS 1293:2019

भारतीय मानक ब्यूरो BUREAU OF INDIAN STANDARDS

FMCD

1	Ampere & Voltage rating	2.5 A, 250V, AC	6 A, 250V, AC	16 A. 250V. AC
2	Rewireable/Non Rewireable	Non Rewireable	Non Rewireable	Non Rewireable
3	No. of Pin	2 pin	3pin	Principal and the second secon
4	Round/Flat	Round	Round	3 pin
5	Solid/not solid	Solid	Solid	Round
6	With/without sleeves	With insulating sleeves	Without insulating sleeves	Without insulating
,	No. of poles (with/ without carthing contact)	contact	2 poles With earning contact	2 poles with earthing
5	Type of terminal (Screw type/ Screw less terminals for rigid conductors/ Screw less terminals for rigid & flexible conductors)	rigid and flevible	Screwless terminals for rigid and flexible conductors	Screwless terminals for rigid and flexible conductors
9	Suitable for class I/II appliances	for class II appliances		
10	Degree of protection	IPX0	for class I appliances	for class I appliances
112		11 70	i i X 2	IPX0

Other terms and conditions of Licence remain the same